

4 p W M g t a d d o S W i g i n a w p o d i V a g s o e t i s s l o v [ w y S a i z i n r n d V a a d i a

F c W 4 B \* # \* \_ W W o n o c W Y g a T S g n S a W o t

d W [ i a a d U W V [ i n p g S o [ a i z : o p o [ g [ u W n S i

U d W W b S Y W V [ n o S i U W a a \* o p e r a t i n g t e m p e r a t u r e : - 5 5 ° C ~ 1 2 5 ° C

H 3 5 ž 5 W d o [ a [ W V T t P > 1 \$ % 1 \* 1 F P H / ; 7

H 6 7 / ; 7 5 1 " ) & ) f i a a d n S a W o t d W Y p g S o [ a

Feature

Magnetic coupling with stable performance

Wide operating temperature: -55°C ~ 125°C

No bias current required, reduces standby power consumption

Up to 5000 VAC isolation voltage  
Creepage distance >8 mm

UL62368 and TUV (IEC62368) certification

CQC certification per GB4943.1-2022


VDE (IEC60747) approved

Applications

QC / USB PD / programable AC/DC chargers

Adapters

AC/DC auxiliary power



LSOP-4 package

Electrical Schematic




Figure 1. Electrical Schematic

BP

